








Type	Visuel	C (base platine) mm	A (H mini) mm	B (H max) mm	Percage central mm	Charge maxi kN	Clef de manœuvre	Condisc	Poids Kg
KS 2025		80x80	25	35			55	-	0,7
KS 4035		80x80	35	47		200	55	-	0,85
KS 4035 C condisc®		80x80	35	47		200	55	x	0,85
KS 4035 D		80x80	35	47	18	200	55	x	0,8
KS 4035 DC condisc®		80x80	35	47	18	200	55	x	0,8
KS 4040		80x80	40	57		200	55	-	0,95
KS 4040 C condisc®		80x80	40	57		200	55	x	0,95
KS4040D		80x80	40	57	18	200	55	x	0,9
KS 4040 DC condisc®		80x80	40	57	18	200	55	x	0,9
KS 4045		80x80	45	67		200	55	-	1,05
KS 4045 C condisc®		80x80	45	67		200	55	x	1,05
KS 4045 D		80x80	45	67	18	200	55	x	0,96
KS 4045 DC condisc®		80x80	45	67	18	200	55	x	0,96
KS SF condisc®		80x80x24	60	80		200	55	x	1,9
KS 9045 C condisc®		110x110	50	70		400	75	x	2,2
KS 9060 C condisc®		110x110	60	85		400	75	x	2,7
KS 9060 DC condisc®		110x110	60	85	30	400	75	x	2,5

